



Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** EPOXY COATING 308 PART B
- **Article number:** 577-035
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 No further relevant information available.
- **Application of the substance / the mixture** Hardener.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** TAMBOUR LTD.
- **Further information obtainable from:** Health & Safety
- **1.4 Emergency telephone number:** *6477

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Muta. 2 H341 Suspected of causing genetic defects.
 Carc. 1B H350 May cause cancer.
 Repr. 1B H360Df May damage the unborn child. Suspected of damaging fertility.
 STOT SE 1 H370 Causes damage to organs.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 1)

· 2.2 Label elements**· Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms GHS02, GHS07, GHS08, GHS09**· Signal word** Danger**· Hazard-determining components of labelling:**

4,4'-diaminodiphenylmethane

dibutyl phthalate

· Hazard statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360Df May damage the unborn child. Suspected of damaging fertility.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterisation: Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 84-74-2 EINECS: 201-557-4	dibutyl phthalate ⚠ Repr. 1B, H360Df; ⚠ Aquatic Acute 1, H400	25-50%
CAS: 101-77-9 EINECS: 202-974-4	4,4'-diaminodiphenylmethane ⚠ Muta. 2, H341; ⚠ Carc. 1B, H350; ⚠ STOT SE 1, H370; ⚠ STOT RE 2, H373; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; ⚠ Skin Sens. 1, H317	25-50%
CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix) ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315	2.5-10%

· SVHC

84-74-2	dibutyl phthalate
101-77-9	4,4'-diaminodiphenylmethane

· Additional information: For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
 Immediately remove any clothing soiled by the product.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
 Immediately wash with water and soap and rinse thoroughly.
 Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
 Do not allow product to reach sewage system or any water course.
 Prevent seepage into sewage system, workpits and cellars.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.

(Contd. on page 4)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 3)

Prevent formation of aerosols.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep container tightly sealed.

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

84-74-2 dibutyl phthalate

WEL (Great Britain)	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³
---------------------	--

101-77-9 4,4'-diaminodiphenylmethane

WEL (Great Britain)	Long-term value: 0.08 mg/m ³ , 0.01 ppm Carc; Sk, BMGV
---------------------	--

1330-20-7 xylene (mix)

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
TLV (Israel)	Short-term value: 150 ppm Long-term value: 100 ppm

- **Ingredients with biological limit values:**

101-77-9 4,4'-diaminodiphenylmethane

BMGV (Great Britain)	50 µmol/mol creatinine Medium: urine Sampling time: post shift for inhalation and pre-shift next day for dermal exposure Parameter: total MDA
----------------------	--

1330-20-7 xylene (mix)

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 4)

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:**

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	137 °C

· Flash point: 30 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 390 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.

· Explosion limits:

Lower:	0.1 Vol %
Upper:	2.0 Vol %

· Vapour pressure at 20 °C: 0.1 hPa

· Density: Not determined.

(Contd. on page 6)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 5)

· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	6.2 %
Water:	0.0 %
VOC Content	6.2 %
Solids content:	56.4 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if swallowed.

· **LD/LC50 values relevant for classification:****84-74-2 dibutyl phthalate**

Oral	LD50	8000 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rbt)

101-77-9 4,4'-diaminodiphenylmethane

Oral	LD50	347 mg/kg (rat)
------	------	-----------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity**
Suspected of causing genetic defects.
- **Carcinogenicity**
May cause cancer.
- **Reproductive toxicity**
May damage the unborn child. Suspected of damaging fertility.

(Contd. on page 7)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 6)

- **STOT-single exposure**
Causes damage to organs.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:**
Very toxic for fish
Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---------------------------------------|---|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1992 |
| · 14.2 UN proper shipping name | |
| · ADR | 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (XYLENES, 4, 4'-DIAMINODIPHENYLMETHANE), ENVIRONMENTALLY HAZARDOUS |
| · IMDG | FLAMMABLE LIQUID, TOXIC, N.O.S. (XYLENES, 4,4'-DIAMINODIPHENYLMETHANE), MARINE POLLUTANT |
| · IATA | FLAMMABLE LIQUID, TOXIC, N.O.S. (XYLENES, 4,4'-DIAMINODIPHENYLMETHANE) |

(Contd. on page 8)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR



· Class 3 Flammable liquids.
 · Label 3+6.1

· IMDG



· Class 3 Flammable liquids.
 · Label 3/6.1

· IATA



· Class 3 Flammable liquids.
 · Label 3 (6.1)

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards:

Product contains environmentally hazardous substances:
 dibutyl phthalate, 4,4'-diaminodiphenylmethane

· Marine pollutant:

Yes
 Symbol (fish and tree)

· Special marking (ADR):

Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Danger code (Kemler):

36

· EMS Number:

F-E,S-D

· Stowage Category

A

· 14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

D/E

· IMDG

· Limited quantities (LQ)

5L

(Contd. on page 9)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 8)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (XYLENES, 4,4'-DIAMINODIPHENYLMETHANE), 3 (6.1), III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07, GHS08, GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:**
4,4'-diaminodiphenylmethane
dibutyl phthalate
- **Hazard statements**
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H360Df May damage the unborn child. Suspected of damaging fertility.
H370 Causes damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
H3 STOT SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE
E1 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 28, 30, 40, 43, 51b
- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials, Annex II:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.

(Contd. on page 10)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 9)

· **Technical instructions (air):**

Class	Share in %
I	65.5
NK	6.2

· **Waterhazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.· **Other regulations, limitations and prohibitive regulations**· **Substances of very high concern (SVHC) according to REACH, Article 57**

84-74-2	dibutyl phthalate
101-77-9	4,4'-diaminodiphenylmethane

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H332 Harmful if inhaled.
 H341 Suspected of causing genetic defects.
 H350 May cause cancer.
 H360Df May damage the unborn child. Suspected of damaging fertility.
 H370 Causes damage to organs.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Tambour Ltd.- Health & Safety Department.· **Contact:**

Moti Adler
 Phone: +972(4)985-3795
 e-mail: motiA@tambour.co.il

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organisation
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 11)

Safety data sheet
Conform to Regulation EC No. 1907/2006 amended by Regulation
(EU) No. 453/2010

Printing date 24.01.2019

Version number 1

Revision: 24.01.2019

Trade name: EPOXY COATING 308 PART B

(Contd. of page 10)

*Skin Sens. 1: Skin sensitisation – Category 1**Muta. 2: Germ cell mutagenicity – Category 2**Carc. 1B: Carcinogenicity – Category 1B**Repr. 1B: Reproductive toxicity – Category 1B**STOT SE 1: Specific target organ toxicity (single exposure) – Category 1**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**· * **Data compared to the previous version altered.***

GB